

# RENOLIT ALKORPLUS<sup>81008</sup>

## Protection and separation layer



### PRODUCT DESCRIPTION

Needlefelt synthetic fleece for use in **RENOLIT** roofing systems.

### CHARACTERISTICS

Material	synthetic fleece (short fibre): 180 g/m <sup>2</sup>	EN 9864
Thickness 2 kPa	average 0,8 mm	EN 9863
Colour	light green	

### TECHNICAL PROPERTIES

#### • Mechanical properties

Tensile strength	M	MLV: 3 kN/m according to EN 10319
	C	MLV: 3 kN/m according to EN 10319
Elongation (±20 %)	M	MLV: 64 % according to EN 10319
	C	MLV: 82 % according to EN 10319

- Meets all requirements for protection and separation layers
- Will not rot

### FIELD OF APPLICATION

- As a separation layer when applying **RENOLIT ALKORPLAN** on a bituminous surface or on insulation such as expanded or extruded polystyrene for ballasted or mechanically fixed systems (except in the case of inverted roofs on extruded polystyrene)
- As a protective layer
- As a compression layer
- Can be used on all common surfaces
- According to the system guidelines **RENOLIT ALKORPLAN** - **RENOLIT ALKORTOP** - **RENOLIT ALKORTEC**

### PACKAGING

	Width	Length	Weight	Weight per standard roll
Delivery from stock	2 m	100 m	180 g/m <sup>2</sup>	36 kg/roll

### STORAGE

- Rolls are singly packed and wrapped in polyethylene film.

[WWW.RENOLIT.COM/ROOFING](http://WWW.RENOLIT.COM/ROOFING)

**RENOLIT** Cramlington Ltd, Station Road - Cramlington, Northumberland NE23 8AQ - United Kingdom  
T +44 1670 718283 - F +44 1670 719367 - [renolit.cramlington@renolit.com](mailto:renolit.cramlington@renolit.com)

**RENOLIT** Belgium N.V. - Export Dpt. - Industriepark De Bruwaan 43 - 9700 Oudenaarde - Belgium  
T +32 (0)55 33 98 51 - F +32 (0)55 31 86 58 - [renolit.belgium@renolit.com](mailto:renolit.belgium@renolit.com)



*Rely on it.*