## ALKORPLUS CLEANER<sub>81044</sub>

# Cleaner for RENOLIT ALKORPLAN and RENOLIT ALKORTEC membranes



#### PRODUCT DESCRIPTION

Cleaning of welding areas, removal of building dirt and stains (bituminous products, adhesive residue, etc.) during installation of **RENOLIT** ALKORPLAN and ALKORTEC membranes. The ALKORPLUS Cleaner is not to be used as a general membrane cleaner.

#### CHADACTEDISTICS

Appearance	Liquid	
Colour	Colourless, transparent	
Density	0,9 g/cm <sup>3</sup>	
Flashpoint	-4 °C	
Consumption	10 - 50 g/lm seam joint depending on the degree of soiling.	
Volatile organic compound (VOC) content	100 %	

#### INSTRUCTIONS FOR USE

- Wearing protective gloves, apply ALKORPLUS Cleaner on a soft and clean cloth. Rub the wet cloth on the area to be cleaned and wipe dry with a second soft and clean cloth. Remove the dirt in one direction, away from the overlap. Persistent soiling may require repeating the above operation.
- Allow the cleaner to evaporate completely before starting hot air welding.
- After use close the tin immediately.
- Do not pour ALKORPLUS Cleaner directly on the RENOLIT ALKORPLAN or ALKORTEC membranes.

CAUTION: ALKORPLUS Cleaner will remove the lacquer coating from lacquered RENOLIT membranes and should only be used as specified.

#### PACKAGING

Туре	Content	Packaging unit
81044-001	1 litre	6 tins / box LQ 🔷
81044-002	5 litre	tin

#### STORAGI

- Keep away from heat and sources of ignition.
- Keep away from direct sunlight.
- Keep only in the original container in a cool, well ventilated place.
- Shelf life: min. 12 months in original unopened packaging.
- Refer to the text on the label and take into consideration the Safety Data Sheet.

### TRANSPORT

- Proper shipping name: Ethyl Acetate
- Transport hazard class 3 PKg Gr. II UN Nr: 1173

## WWW.RENOLIT.COM/ROOFING

**RENOLIT** RENOLIT Cramlington Ltd, Station Road - Cramlington, Northumberland NE23 8AQ - United Kingdom T +44 1670 718283 - F +44 1670 590096 - renolit.cramlington@renolit.com

